

Technical info on the aluminium doors.

- Doors manufactured from high performance 36mm thick aluminium composite panels featuring two pressed aluminium panels with insulated core.
- Frame manufactured in industry leading Schuco ADS 70 high insulation system.
- Solid and glazed options.
- Glazed options feature 36mm triple-glazed unit, fully bonded and held into place with an internal bezel.
- 1.2w/m²K with frame as completed door set (panel achieves a U-value of just 0.9w/m²K)
- High quality rubber seals deliver excellent weather tightness.
- Threshold – Part M (disabled access) compliant as standard.
- Single doors can be manufactured up to 1208mm wide and 2370 high.
- German engineered locking systems with automatic locking as standard in line with Secured by Design.
- All doors are pre-hung and fully tested before shipping to guarantee peace of mind on installation.
- Panels: 36mm thick aluminium composite panels featuring two pressed aluminium panels with insulated core.
- Solid and glazed options achieving a U-value of just 0.9w/m²K
- Panels can be manufactured up to 850mm wide and 2,050mm high (excludes frame).
- Choice of 90 different panels

We genuinely believe that there isn't a better entrance door on the market. We check and double check panels and completed door sets prior to shipping and then pack and prepare them with the same demanding attention to detail.

We know that you or your customers don't want surprises on site which is why we take every care in what we do.

System accreditations:

- Manufactured to meet EN 12207;2000 AIR CLASS 4
- Achieves EN 12207;2000 WATER CLASS 6a
- EN 12207;2000 WIND CLASS C4
- Hinges and mechanisms cycle tested to 50,000 operations

Also to this for the lantern page can you place in the download button for brochure same as the old website.